

PREP & SPILL CONTROL PADS



Our absorbent, triple-layered pads are ideal for use in cleanrooms and controlled environments. Perfect for use as tray or workstation liners or to absorb spills when areas must be critically clean.

FEATURES AND BENEFITS

- Three-layer construction provides optimal absorption and a liquid barrier
- Non-stick aperatured polypropylene coating effectively absorbs liquid while reducing linting
- Airlaid absorbent middle layer provides 790% total absorbency
- Low density polyethylene (PE) film backing blocks liquids from spreading to surfaces
- Free of latex and solvent-based adhesives

Cleanroom Level Recommendation*

ISO



QUALITY STANDARDS

FG Clean Wipes is a pioneer of critical cleaning products. Quality is a prerequisite to everything we make. That means the dependability and performance of our prep and spill control pads are unmatched.

**THIS SPECIALIZED
PRODUCT IS AVAILABLE
IN THE FOLLOWING SIZES
AND CAN BE CUSTOMIZED
BY REQUEST**

ITEM NO.	SIZE	STANDARD PACKAGING
7-SPTAFL-00	11" x 16" 28 x 40.5 cm	50/bag 4 bags/case
7-SPTFML-00	16" x 22" 40.5 x 56 cm	50/bag 4 bags/case

* Also available Gamma Irradiated

* The above recommendations are based on typical industry wide applications based on general cleanroom cleanliness classifications. Please consult our experienced FG Clean Wipes sales representatives for specific cleanroom product selections for critical and/or specialized applications based on a wider range of selection criteria.



No matter your industry, we have the optimal critical cleaning solution.
Find out more information at www.FGCleanWipes.com

Phone: +1 (413) 598-8344
Fax: +1 (413) 592-4112

PREP & SPILL CONTROL PADS

PREP & SPILL CONTROL PADS PP DELNET NETTING / AIRLAID WOOD PULP & BINDER / PE FILM

PROPERTY	TYPICAL VALUE
Basis Weight	155 gsm
Total Absorbency	790% (12.25 g / 1.55 g)
Total Absorption	7-SPTAFL-00: 11" x 16" (28 x 40.5 cm) - 139g of water 7-SPTFML-00: 16" x 22" (40.5 x 56 cm) - 278g of water
Elemendor Tear	MD 377 g TD 160 g
Tensile Yield	MD 6.44 lbs (2.92 kg) TD 6.03 lbs (2.74 kg)
Tensile Break	MD 3.61 lbs (1.64 kg) TD 4.81 lbs (2.18 kg)
Elongation	MD 745% TD 155%

Notes

1. Data shown are typical values and should not be used as product specifications.
2. Total absorbency percentage is weight of water absorbed divided by sample weight.